



TOLL FREE 1-866-545-6484 www.mitico.com
services@mitico.com / sales@mitico.com



DOMED PB/PBRV SERIES

Jawless Immobilizers

APPLICATION/USE: Unsurpassed **Extra Heavy Duty**, unattended, on/off street, municipal, campus, private, corporate and anti-theft applications.

FEATURES MITI'S UNIQUE PATENTED "HOOK-LOC" & "VARIABLE TIRE STOPS" ATTACHMENT SYSTEM

Domed PB ENFORCER Series "Hook-Loc with Variable Tire Stops" models feature a built-in lock system, unitized construction, and install in 30-45 seconds. No assembly required. Deters forcible removal with double gauge 2" x 2" tubular box steel construction. The reinforced design eliminates the possibility of damage, scratching or marring of the vehicle's wheel rim edge (flange). The "Hook-Loc" attachment system is found only on Rhino Immobilizers.

- Attachment by means of wheel rim edges (flanges) through attachment jaws is totally eliminated with the Rhino PB/PBRV series immobilizers. The inner "Hook-Loc" arm, with pressure stop affixed to the outer side, indexes quickly within the inner wheel's cavity between the backing plate or wheel drum.
- An assist spring aids in the installation of the immobilizer by holding the inner "Hook-Loc" arm against the inner wheel, where it is indexed between the wheel and brake backing plate.
- Stacking tire stop prevents side-to-side movement of the immobilizer and deters attempts at forced removal or drive-away. Attaches to small, medium or oversized tires and wheels.
- Bi-directional stand design allows the immobilizer to be attached to any vehicle wheel – front, rear, left or right side. Unique to Rhino.
- Each unit shipped with a Secur-Key and package of immobilization tags.



6 Telescoping dome assembly with protective beading prevents removal of the wheel.

7 Baked-on environmentally safe safety orange powder coating provides high visibility and superior rust protection.

8 Deep dish dome provides space for protruding hubs. Prevents access to lug nuts.

MADE IN USA

9 MITI-Rhino's stainless steel Secur-Bolt-Key system provides for secure immobilizer attachment. Built-in padlock provided. Unique design deters unauthorized removal of wheel or immobilizer. When tightened, the Secur-Bolt applies pressure against the inner rotating "Hook-Loc" arm, rotating it inward until it is stopped when the arm's affixed pressure stop comes into contact with the wheel's brake backing plate, wheel drum or tie rod end. The inward pressure is then reversed at the stop, driving the outer affixed and telescoping dome assembly against the outer wheel or hubcap for a positive vice-like attachment.

DOMED PB/PBRV SERIES MODELS "ENFORCER"

PB FITS USA, foreign subcompact to full size, light trucks, standard-sized wheels.
PBRV FITS USA, foreign subcompact to full size, light trucks, oversized wheels.

DOMED WHEEL COVERS 10" (25.40cm) 12" (30.48cm) 14" (35.56cm) 15" (40.24cm)

PBRV-10 WHEEL/TIRE 2 to 12" (5.08 - 30.48cm) WIDE X **12 to 16 1/2"** (30.48 - 41.91cm) DIAMETER

UNIT SIZE	(WIDTH)	(LENGTH)	(HEIGHT)	(WEIGHT)
	13 1/4" (33.66cm)	x 30 1/2" (77.47cm)	x 10" (25.40cm)	27 1/2 lbs (10.55kg)
PACKAGED 1 PER BOX	13" (33.02cm)	x 31 1/2" (80.01cm)	x 12" (30.48cm)	34 lbs (15.42g)
PACKAGED 2 PER BOX	13" (33.02cm)	x 31 1/2" (80.01cm)	x 12" (30.48cm)	43 lbs (19.501kg)

PBRV-12 WHEEL/TIRE 2 to 17 1/2" (5.08 - 44.45cm) WIDE X **12 to 24"** (30.48 - 60.96cm) DIAMETER

UNIT SIZE	(WIDTH)	(LENGTH)	(HEIGHT)	(WEIGHT)
	13 1/4" (33.66cm)	x 32" (81.28cm)	x 12" (30.48cm)	28 1/2 lbs (12.93kg)
PACKAGED 1 PER BOX	13" (33.02cm)	x 31 1/2" (80.01cm)	x 12" (30.48cm)	36 lbs (16.33kg)
PACKAGED 2 PER BOX	13" (33.02cm)	x 31 1/2" (80.01cm)	x 12" (30.48cm)	67 lbs (30.39kg)

PBRV-14 WHEEL/TIRE 2 to 17 1/2" (5.08 - 44.45cm) WIDE X **12 to 24"** (30.48 - 60.96cm) DIAMETER

UNIT SIZE	(WIDTH)	(LENGTH)	(HEIGHT)	(WEIGHT)
	13 1/4" (33.66cm)	x 33 1/2" (85.09cm)	x 14" (35.36cm)	29 1/2 lbs (13.38kg)
PACKAGED 1 PER BOX	13" (33.02cm)	x 31 1/2" (80.01cm)	x 12" (30.48cm)	36 lbs (16.33kg)
PACKAGED 2 PER BOX	13" (33.02cm)	x 31 1/2" (80.01cm)	x 15" (38.10cm)	66 1/2 lbs (30.16kg)

PBRV-15 WHEEL/TIRE 2 to 17 1/2" (5.08 - 44.45cm) WIDE X **12 to 24"** (30.48 - 60.96cm) DIAMETER

UNIT SIZE	(WIDTH)	(LENGTH)	(HEIGHT)	(WEIGHT)
	13 1/4" (33.66cm)	x 34" (86.36cm)	x 16" (40.64cm)	30 1/2 lbs (13.83kg)
PACKAGED 1 PER BOX	13" (33.02cm)	x 31 1/2" (80.01cm)	x 15" (38.10cm)	37 lbs (16.78kg)



NOTE: 14/15" domed wheel covers are ideal for large diameter wheels, 12" are best for general use on all diameters, and 10" are ideal for extremely small diameter wheels. 15" are primarily used for municipal applications.

US PATENTS 6,032,497 / 5,865,048

ORDER FORM
- PAGE 15 -



Immobilize to Stop Equipment Theft

